



Remorca profesioniștilor

REMORCI DE TRANSPORT FURAJE

TIP	SLW 20 R	SLW 20 TR	SLW 25 TD	SLW 30 TN	SLW 40 TN
Greutate admisa	8000 kg	8000 kg	12000 kg	18000 kg	20000 kg
Greutate incarcatura	5600 kg	5500 kg	8200 kg	12500 kg	14000 kg
Capacitate bena	20 m ³	20 m ³	25 m ³	32 m ³	38 m ³
Dimensiuni bena L X l	5,4 x 2,1	5,4 x 2,1	6,2 x 2,1	6,5 x 2,3	7,2 x 2,3
Inaltime perete	1700 mm	1700 mm	1900 mm	2100 mm	2300 mm
Inaltime totala	3190 mm	3100 mm	3450 mm	3750 mm	3950 mm
Dimensiuni totale	7,4 x 2,3	7,3 x 2,3	7,9 x 2,55	8,4 x 2,55	8,9 x 2,55
Sasiu	2 axe suspensie	Tandem cu susp. Paralel	Tandem cu susp. Paralel	Tandem-LK su susp. Papalel	Tandem-LK cu susp. Paralel
Frana	Inertiala	Inertiala	Pneumatica 2 circuite	Pneumatica 2 circuite	Pneumatica 2 circuite
Echipeare anvelope	15,0/70 x 20	15,0/70 x 18	550/60 x 22,5	550/60 x 22,5	600/55 x 22,5
Valturi doza	Optional	Optional	Optional	2 Valturi	2 Valturi

REMORCI DE TRANSPORT CEREALE

TIP	SMK 10/40	MK 20/40	MK 29/40	MK 32/40
Greutate admisa	20000 kg	20000 kg	29000 kg	32000 kg
Greutate incarcatura	ca. 14000 kg	ca. 14400 kg	ca. 21000 kg	ca. 23000 kg
Sistem agatare	inf/sup	inf/sup	inf/sup	inf/sup
Necesar ulei	34 Litri	35 Litri	64 Litri	65 Litri
Dimensiuni bena	5,0/2,2/0,8	6,3/2,2/1,4	7,2/2,2/1,5	8,0/2,2/1,6
Suprainaltatori siloz	500 mm	500 mm	500 mm	500 mm
Sistem suspensie	24 to parabel	24 to parabel	30 to parabel	36 to parabel
Anvelope	600/55 x 22,5	600/55 x 22,5	600/55 x 26,5	700/50 x 26,5

REMORCI DE TRANSPORT CU SNEC

Typ	ULW 3000 T	ULW 2500 T	ULW 2000 T	ULW 1500 E	ULW 1200 E
Constructie	Tridem compensare dinamica	Tandem compensare dinamica	Tandem compensare dinamica	Monoax cu suspensie	Monoax cu suspensie
Frana	Pneumatica 2 circuite	Pneumatica 2 circuite	Pneumatica 2 circuite	Pneumatica 2 circuite	Pneumatica 2 circuite
Anvelope	800/45x26,5 12PR				
Capacitate bena mc	32		25	16	12
Lungime bena mm	7200		6000	4500	4000
Latime bena mm	2500		2500	2500	2500
Lungime totala mm	10100		8550	7050	6550
Latime totala mm	2950		2950	2950	2800
Inaltime max. mm	3600		3550	3250	2980
Diametru melc mm	500		420	420	365
Inaltime descarcare mm	4400		4400	4400	4200
Viteza descarcare to/h	450		200-400	200-402	150-200
Greutate max admisa	29000		22000	20000	12000
Viteza maxima	40 Km/h - ALB		25	25	25