

CLAAS

ROLLANT VARIANT



www.agrocomert.ro



Centrul Timișoara: Str. C. Brediceanu nr.2, cod 300077
Tel: +40-256-430317 Fax: +40-256-434098
e-mail: ahctim@agrocomert.rdstm.ro

*Intotdeauna
slături
de timp*

ROLLANT	260	340 R	350 R	350 RC	354 RF	354 RC	355 RC	355 RC Comfort	355 RC Uniwrap
Turație la PTO	540	540	540	540	540	540	540	540	540
Lățime masei de lucru	m	1.85	2.1	2.1	1.85 / 2.10	1.85 / 2.10	2.1	2.1	2.1
Diametrul camerei de presare	m	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Lățimea camerei de presare	m	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
Număr de tamburi	17	16	16	16	16	16	16	16	16
Înălțime	m	2.61	2.31	2.31	2.31	2.31	2.31	2.31	2.83
Lățime	m	2.5	2.33-2.77	2.33-2.77	2.33-2.77	2.33-2.77	2.33-2.77	2.58-2.77	2.83
Lungime	m	4.86	4.72	4.72	4.72	4.72	4.72	4.72	6.69
Greutate	kg	2240							
Terminal de control	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS	Terminal Standard CLAAS
Înzățitor folie	-	-	-	-	-	-	-	-	2 X 750mm
Stoc folie	-	-	-	-	-	-	-	-	12 tamburi
Preîncalzire	-	-	-	-	-	-	-	-	67% (82% optional)
Anvelopare	11,5/80-15,3 10 PR (●) 11,5/80-15,3 10 PR (●) 11,5/80-15,3 10 PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	11,5/80-15,3 10 PR (●) 11,5/80-15,3 10 PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	11,5/80-15,3 10 PR (●) 11,5/80-15,3 10 PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	11,5/80-15,3 8PR (●) 11,5/80-15,3 8PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○) 500/45-22,5 12 PR (○)	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/45-22,5 12 PR (○)	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/45-22,5 12 PR (○)	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/45-22,5 12 PR (○)	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/45-22,5 12 PR (○)

VARIANT	350	360 RC	365 RC	370	380 RC	385 RC
Turație la PTO	540/1000	540/1000	1000	540/1000	540	1000
Lățime masei de lucru	m	2.1	2.1	2.1	2.1	2.1
Ridicarea masei de lucru	hidraulic	hidraulic	hidraulic	hidraulic	hidraulic	hidraulic
Diametrul balotului	m	0,9-1,55	0,9-1,58	0,9-1,8	0,9-1,8	0,9-1,8
Lățimea balotului	m	1,2	1,2	1,2	1,2	1,2
Camara presare	variabilă 5 curele	variabilă 4 curele	variabilă 4 curele	variabilă 5 curele	variabilă 4 curele	variabilă 4 curele
Anvelopare	11,5/80-15,3 8PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○) 500/50-17 F+	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/50-17 F+	15,0/55-17 10 PR (●) 19,0/45-17 10 PR (○) 500/50-17 F+	11,5/80-15,3 8PR (●) 11,5/80-15,3 8PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	11,5/80-15,3 8PR (●) 11,5/80-15,3 8PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)	11,5/80-15,3 8PR (●) 11,5/80-15,3 8PR (●) 15,0/55-17 10 PR (○) 19,0/45-17 10 PR (○)
Lungime cu rampă baloți	m	4,68	4,68	4,68	4,68	4,68
Lățime cu cauciucuri 15,0/55-17	m	2,49	2,49	2,49	2,49	2,49
Lățime cu cauciucuri 19,0/45-17	m	2,66	2,66	2,66	2,66	2,66
Înălțime	m	2,79-2,83	2,79-2,83	2,99-3,03	2,99-3,03	2,99-3,03
Terminal de control standard	●	●	●	●	●	●
Terminal de control mediu	○	○	○	○	○	○
CLAAS COMMUNICATOR	○	○	○	○	○	○

Legendă
 ● standard
 ○ opțional
 - nu este disponibil



*Intotdeauna
a datarii de timp*

Centrul Timișoara: Str. C. Brediceanu nr.2, cod 300077

Tel: +40-256-430317 Fax: +40-256-434098

e-mail: ahctim@agrocomert.rdstm.ro